

Republic of the Philippines Department of Labor and Employment REGIONAL OFFICE NO. APPLICATION TO CONSTRUCT HOISTWAY AND INSTALL GATES OR DOORS

١.	Owner/Establishment:				
2.	Address:				
3,	Company Tel. No Owner/Manager:				
ŧ.	Building where Elevator/Manlift/Dumbwaiter is to be installed:				
	No. of stories				
i.	Name and signature of person to supervise installation of hoistways, etc.				
	Board of Mechanical Engineering	Reg. NoLicen	se No.		
5.	When was building erected	Installation is an a	ddition		
	Addition erected, when				
7.	Hoistway: New;exist	ing	_; alteration		
3.	Elevator: Freight	; Passenger			
		Automatic Push Button			
		Constant-Pressure Push Button			
		Other Control			
		HOISTWAY			
١.	Fireproof enclosure	Material			
			(Concrete, tile, b	rick)	
	Minimum thickness	Entire height			
0.	Non-fireproof enclosure	Materials			
		(V	Vells, mesh work, grille-s	latted partitions	
	Height: Floor to ceiling landing sides				
			(above floor other s	ides)	
1.	Hoistway roof: Material(Wood-cond	Thickness			
	(Wood-cond	crete)			
	metal frame skylight % the area of shaft (yes or	lan.			
2	Exterior window with metal frame and sash at top of hoistway				
-	Above platform	Immediately below platform			
3	Above platform How gu	arded	any recesses		
٠.	(yes or no)	0.000	any recourses	(yes or no)	
	(yes or no)	How as	arded		
4	Penthouse	Minimum headroom	anded		
-	PenthouseMinimum headroom Height entrance above building roof				
15	Access to penthouse from roofBy iron stairs or ladder				
10.	(yes or no)				
10	Angle or iron stairs or ladder less than 60 degrees from horizontal				
υ.	Angle or iron stairs or ladder less than 60 degrees from horizontal				
	Electric light in penthouse Electric light at all landings (ves.or.no)				
κ.	(yes or no)	Electric light at all lar		\	
	(900 01 110)		(yes o		
Ö.	Size of hoistway	H 6			
	Nonslip threshold 18 inches wide from hoistway	line (yes or no)			
	Across entire width (yes or no)				
9.	Distance lowest landing to bottom of pit	adjacent h	oistways		
	Partition between	height			
	но	ISTWAYGATES			
0.	Hinged	Slide			
	(specify floors)		(specify floors)		
11.	Manually operated	Self-closing by a	ction of car		
	Full automatic	Power driven			
	Contact	Interlock	Type of designation		
	Made by		,,		
4	Emergency release for contact or interlock				
*					
15	Locks on gates all floors	e of designation Made by ks on gates all floors Openable by key floor slide			
	Var. hav at hattans landing				
26	Height of gates Spacing between slats 2" or less				
-	Hadasalaasanaa ubaa dawa				
7	Gates all landings		Distance, inside of gate	to hoistway line	
	Cates an ianum go	Gate counterweight guarded	Dicialitie, make of gave	to motorway illie	
		Sale counterweight guarded _			

		HOISTWAY DOORS				
28.	Fire doors	Type designation				
	Made by	- //				
29.	Hinged	Slide				
	(:	specify floors) (specify floors)				
30.		Self-closing by action of car				
31.	Full automatic	Power driven				
32	Contact Interlo	kType of designation				
	Made by	-,,,				
33.	Emergency release for contact of interlock					
	Type of designation	Made byOpenable by key floor side				
34.	Locks on doors all floors	Openable by key floor side				
	Key box at bottom landing					
35.		Distance, insider of door to hoistway line				
	Door counterweights guarded					
		AUTOMATIC TRAP DOORS				
36.	Automatic trap doors	Floors				
37.	7. Standard railing Distance to hoistway					
	All floors					
		Name & Signature of Owner/Manager				
		Establishment				
EVI	DL No.					
Pla	n Fee					

NOTE:

O. R. No. ____ Date Date Received Received by ___

The detailed working drawing of the hoistway, gates, doors and installation plans shall accompany this application and shall be prepared, signed and sealed by a PROFESSIONAL MECHANICAL ENGINEER.